

PROJECT:	QTY:	ITEM No.
----------	------	----------

# CTC4036

## COMBINATION DRY/REFRIGERATED UNDERCOUNTER DISPLAY CASE

**REFRIGERATED CROSS SECTION**

- FLUORESCENT "SLIMLINE" LIGHT
- THERMOPANE FRONT GLASS
- MIRRORED INSIDE GABLES
- GLASS SHELVES
- STAINLESS STEEL PAN
- PLASTIC LAMINATED FRONT
- PLASTIC LAMINATED TOP
- COMPRESSOR
- PLASTIC LAMINATE FRONT FACE

Dimensions: 18 3/8", 18.5", 21", 25 1/2", 36", 10 1/2", 5 3/4", 4 1/2", 30 3/4"

**BACK VIEW**

- PLASTIC LAMINATED BODY
- ONEWAY MIRRORED THERMOPANE HINGED GLASS DOOR
- ELECTRICAL CORD
- LIGHT SWITCH
- BALLAST BOX
- COMPRESSOR
- REMOVABLE GRILL

Dimensions: 40 3/4", 36"

**\* ALL DIMENSIONS ARE ± 1/8"**

\* PICTURE FOR REFERENCE ONLY



*Manufacturers of food service displays*

SPECIFICATIONS						
<b>DIMENSIONS</b>	<b>CTC 4036</b>	MODEL No.	MODEL No.	MODEL No.	MODEL No.	MODEL No.
Length (in)	40.75"	L	L	L	L	L
Depth (in)	30.75"	D	D	D	D	D
Height (in)	36"	H	H	H	H	H
<b>ELECTRICAL</b>						
Voltage	120	120	120	120	120	120
Amperes (Compressor and Light)	12.4	Amps.	Amps.	Amps.	Amps.	Amps.
Amperes (Elect. Cond. Pan needs separate circuit)	-	Amps.	Amps.	Amps.	Amps.	Amps.
Power Cord	8 ft.	8 ft.	8 ft.	8 ft.	8 ft.	8 ft.
<b>NEMA Receptacle Configurations</b>		<b>NOTES</b>				
FOR COMPRESSOR & LIGHTS		All Specifications subject to change without notice.				
<p>125V 5-15R</p>		This Design Is the property of QBD Modular Systems Inc.No copies or reproductions are permitted without the written permission of QBD Modular Systems Inc.  ** All units are designed to operate under normal store conditions of 24°C(75°F) with 50% relative humidity, and maintain the temp. between 35°F to 40°F. **Condensation on glass may occur In Hot / Humld conditions.QBD Is not responsible for any consequential damages as a result. **QBD WARRANTY DOES NOT INCLUDE PRODUCT LOSS OR CONSEQUENTIAL DAMAGES HOWEVER CAUSED. Please review detailed warranty statement prior to purchase.				